

 HASS PIPE

U-PVC WELL PIPES



WELL PIPE ACCESSORIES

Well pipe accessories play a critical role in the proper assembly, installation, and long-term performance of well construction systems. Hasspipe offers a complete range of accessories designed to work seamlessly with U-PVC well casing pipes and screen pipes.

Reducers are used to connect pipes of different diameters, ensuring smooth transitions and system compatibility.

Spurs provide secure end connections and structural support within the well system. Pipe Clamps (Installation Clamps) allow safe handling, lifting, and positioning of pipes during installation, reducing the risk of damage and ensuring installer safety.

Quick-Lock Maneuvering Heads enable fast, controlled, and secure pipe handling during lowering and alignment operations in deep well drilling.

All Hasspipe accessories are manufactured in accordance with TS 11794 standards and inspected under the ISO 9001 quality management system, ensuring durability, precision, and compatibility across all well construction projects.



Spur Dimensions	
Diameter	Material
140	PE
175	PE
200	PE
225	PE
280	PE

Spurs (Bottoom Caps)

This critical component, used at the very bottom of the well string, seals the end of the casing pipe to prevent sediment, sand, or mud from entering the system from the bottom.

Key Function:

Provides a secure seal at the bottom of the well.

Design:

Tapered (conical) shape for easy insertion into the borehole.

Material:

High-quality U-PVC, impact-resistant and non-corrosive.



Reduction Sizes		
D1 mm	D2 mm	Material
175	140	PE
200	175	PE
225	200	PE
280	225	PE

Reducers (Well Casing Reducers)

Used when a transition between two different pipe diameters is required within the same well. It provides a leak-proof and structurally sound connection between large and small diameter pipes.


Key Function:

Offers a seamless transition between different pipe sizes.

Connection:

Features a standard trapezoidal thread system

100% compatible with HASSPIPE systems.



Pipe Clamp Dimensions	
Diameter	Material
140	Iron
175	Iron
200	Iron
225	Iron
250	Iron
280	Iron

Pipe Installation Clamp

A heavy-duty equipment designed to securely hold the pipe string at the wellhead during installation or maintenance. It prevents pipes from slipping into the well while adding new sections.

Key Function:

Safely carries the weight of the entire pipe column during installation.

Material:

Manufactured from high-strength cast iron or steel.

Connection:

Available in various sizes to match different pipe diameters.



Maneuvering Head Dimensions	
Diameter	Material
140	Iron
175	Iron
200	Iron
225	Iron
280	Iron

Quick - Lock Maneuvering Head

A specialized apparatus used to lower or lift the pipe string into the well. Its rapid attachment mechanism at the top of the pipe allows cranes or hoists to transport pipes safely.

Key Function:

Facilitates the vertical lowering or removal of pipes.

Connection:

Features a quick-attach/detach mechanism to save time during installation.