

 HASS PIPE

# U-PVC COLUMN PIPES



### COLUMN PIPE FITTINGS

#### BOTTOM & TOP STAINLESS STEEL ADAPTERS

Bottom & Top Stainless Steel Adapters are designed to provide secure, leak-proof, and durable connections at the lower and upper interface points of column pipe and well systems. Their stainless steel construction ensures high resistance to corrosion and pressure, making them ideal for drilling and groundwater applications.



Diameter	
mm	inch
42	1 1/4"
48	1 1/2"
60	2"
75	2 1/2"
88	3"
113	4"
140	5"
165	6"

ADAPTERS

#### BOTTOM & TOP GALVANIZED STEEL ADAPTERS

Bottom & Top Galvanized Steel Adapters are designed to provide secure, leak-proof, and robust connections at the lower and upper interface points of column pipe and well systems. The galvanized steel construction offers enhanced resistance to corrosion and environmental conditions, ensuring long-lasting and cost-effective performance.



Diameter	
mm	inch
42	1 1/4"
48	1 1/2"
60	2"
75	2 1/2"
88	3"
113	4"
140	5"
165	6"

## COLUMN PIPE TRAP (PIPE HOLDING TOOL)

The Column Pipe Trap is a professional-grade tool designed to securely hold, stabilize and support column pipes during installation and removal in well and drilling applications. Its robust steel construction provides a firm grip, enhancing operational safety and efficiency on site.



Outer Diameter	
mm	inch
42	1 1/4"
48	1 1/2"
60	2"
75	2 1/2"
88	3"
113	4"
140	5"
165	6"

## TIRE TIGHTENING WRENCH

The Tire Tightening Wrench is a practical tool designed for the safe gripping and tightening of PVC column pipes in well and drilling applications. Its strap design provides strong, non-damaging grip the pipe surface. It improves work safety and installation efficiency during assembly and disassembly operations.



Outer Diameter Range	
mm	inch
42 - 165	1 1/4" - 6 1/4"

## MANEUVERING HEAD

The Maneuvering Head is a durable accessory designed for safe lifting and guiding of pipes during drilling and well casing operations. Its swivel mechanism allows the pipe to rotate freely, reducing torsional stress during installation. Compatible with PVC column pipes and drilling pipes, it improves installation efficiency and supports safe operation in deep well applications.



Outer Diameter	
mm	inch
42	1 1/4"
48	1 1/2"
60	2"
75	2 1/2"
88	3"
113	4"
140	5"
165	6"